


SO-1066-10385/10386

ENGINEERING DATA SHEET

RELAY SOCKET
5 AMP





BASIC SOCKET SERIES DESIGNATION FOR:

Series YA

MEETS THE REQUIREMENTS OF:


MIL-DTL-12883

SOCKET DRAWING




HARDWARE MOUNTING

MOUNTING DETAIL 3 PLACES



BOTTOM MOUNT-CLEARANCE HOLE FOR .164 SCREW
TOP MOUNT-CLEARANCE HOLE FOR .112 SCREW
R .05
4 PLACES



MOUNTING DIMENSIONS

GENERAL CHARACTERISTICS

[1]. Supplied with mounting hardware and No. 20 contacts and crimp for coil codes F, K (SO-1066-10385).

[2]. Supplied with mounting hardware and No. 20 contacts and crimp for coil codes E, J (SO-1066-10386).

3. Standard tolerances	.xx ±.01; xxx ±.005.
4. Weight	.055 lb. max
5. Temperature range	-70° C to +125° C



Featuring **LEACH**® power and control solutions
www.esterline.com

AMERICAS
6900 Orangethorpe Ave.
P.O. Box 5032
Buena Park, CA 90622

Tel: (01) 714-736-7599
Fax: (01) 714-670-1145

EUROPE
2 Rue Goethe
57430 Sarralbe
France

Tel: (33) 3 87 97 31 01
Fax: (33) 3 87 97 96 86

ASIA
Units 602-603 6/F Lakeside 1
No.8 Science Park West Avenue
Phase Two, Hong Kong Science Park
Pak Shek Kok, Tai Po, N.T.
Hong Kong
Tel: (852) 2 191 3830
Fax: (852) 2 389 5803

Data sheets are for initial product selection and comparison. Contact Esterline Power Systems prior to choosing a component.