

ENGINEERING DATA SHEET

SERIES 9213

POWER CONTACTOR

3 PST-DM, 50/100 AMP



APPLICATION NOTES:
[103G](#)

Hermetically sealed
 Balanced armature design
 Designed to the performance standards of **MIL-PRF-6106**

PRINCIPLE TECHNICAL CHARACTERISTICS

Contacts rated at **28 Vdc; 115 Vac, 400 Hz, 1Ø**
115/200 Vac, 60/400 Hz, 3Ø

Weight **2.7 lb max**

Dimensions **4.22in x 4.23in x 4.53in**

Special units available upon request

CONTACT ELECTRICAL CHARACTERISTICS

Contact rating per pole and load type [1]	Load current in Amps				
	28 Vdc	115 Vac 400 Hz	115/200 Vac 400 Hz 3Ø WYE OR DELTA	115/200 Vac 60 Hz 3Ø WYE OR DELTA	440 Vac 60/400 Hz
Resistive	100	100	100	50	50
Inductive	100	100	100	50	-
Motor [2]	100	100	100	50	-
Minimum Current	-	-	-	-	-



Featuring **LEACH®** power and control solutions
www.esterline.com

AMERICAS
 6900 Orangethorpe Ave.
 P.O. Box 5032
 Buena Park, CA 90622

Tel: (01) 714-736-7599
 Fax: (01) 714-670-1145

EUROPE
 2 Rue Goethe
 57430 Sarralbe
 France

Tel: (33) 3 87 97 31 01
 Fax: (33) 3 87 97 96 86

ASIA
 Units 602-603 6/F Lakeside 1
 No.8 Science Park West Avenue
 Phase Two, Hong Kong Science Park
 Pak Shek Kok, Tai Po, N.T.
 Hong Kong
 Tel: (852) 2 191 3830
 Fax: (852) 2 389 5803

Data sheets are for initial product selection and comparison. Contact Esterline Power Systems prior to choosing a component.

COIL CHARACTERISTICS (Vdc)**SERIES 9213**

CODE	Vdc	115 Vac 400 Hz	115 Vac 60 Hz
Nominal operating voltage	28	115	115
Maximum operating voltage	29	124	124
Pick-up voltage, max.	18	90	90
Drop-out voltage, max.	7	40	30
Coil resistance ohms $\pm 10\%$ at +25° C	44.5	-	-
Coil current max. mA at +25° C	-	200	200

GENERAL CHARACTERISTICS

Temperature range	-55°C to +71°C
Minimum operating cycles (life) at rated load	50,000
Minimum operating cycles (life) at 25% rated load	100,000
Dielectric strength at sea level	
All circuits to ground and circuit to circuit	1,500 Vrms
Coil to ground	1,250 Vrms
Dielectric strength at altitude 80,000 ft	700 VRMS
Insulation resistance (at 500 Vdc) minimum	100 M Ω min
Sinusoidal vibration (55-500 Hz)	10G
Shock (6-9 millisecond duration)	50G
Maximum contact opening time under shock or vibration	2 μ s
Operate time at nominal voltage	
- DC	30 ms max
- AC	40 ms max
Release time at nominal voltage	
- DC	20 ms max
- AC	60 ms max
Weight, max.	2.70 lb

**CURVES FOR DC VOLTAGES ABOVE NORMAL RATING: RESISTIVE LOAD ONLY
(without arc suppression)**

