



**Application:** Helicopters  
**Function:** Windscreen anti-ice control  
**Characteristics:** Normal control by solid state switching  
28VDC or 115VAC 400 hz switching  
Overheat control by conventional relays  
Input/output on a micro-D connector  
Fault indication  
Dimensions: 180x190x80 mm  
**Features:** Dual independent channels  
Alternative or continuous switching  
Default indicator  
Combines solid state and relay technology



Featuring **LEACH**® power and control solutions  
[www.esterline.com](http://www.esterline.com)

**AMERICAS**  
6900 Orangethorpe Ave.  
P.O. Box 5032  
Buena Park, CA 90622

Tel: (01) 714-736-7599  
Fax: (01) 714-670-1145

**EUROPE**  
2 Rue Goethe  
57430 Sarralbe  
France

Tel: (33) 3 87 97 31 01  
Fax: (33) 3 87 97 96 86

**ASIA**  
Units 602-603 6/F Lakeside 1  
No.8 Science Park West Avenue  
Phase Two, Hong Kong Science Park  
Pak Shek Kok, Tai Po, N.T.  
Hong Kong

Tel: (852) 2 191 3830  
Fax: (852) 2 389 5803

Data sheets are for initial product selection and comparison. Contact Esterline Power Systems prior to choosing a component.