



Application: Rail Transit Systems

Function: Combines subway train switching functions

Characteristics: 19-inch rack, 3U including 44 plug-in relays and time delay relays
 Gaint sockets welded on 4 layers of PCB material
 LED indication for the coil state
 Connection made by DIN41612 connectors on the PCB

Features: Quick connection/disconnection & assembly/disassembly
 Interconnections integrated on the PCB
 All accessory components are welded on the PCB
 Low maintainability level
 Low weight
 Compact size



Featuring LEACH® power and control solutions
www.esterline.com

AMERICAS
 6900 Orangethorpe Ave.
 P.O. Box 5032
 Buena Park, CA 90622

Tel: (01) 714-736-7599
 Fax: (01) 714-670-1145

EUROPE
 2 Rue Goethe
 57430 Sarralbe
 France

Tel: (33) 3 87 97 31 01
 Fax: (33) 3 87 97 96 86

ASIA
 Units 602-603 6/F Lakeside 1
 No.8 Science Park West Avenue
 Phase Two, Hong Kong Science Park
 Pak Shek Kok, Tai Po, N.T.
 Hong Kong
 Tel: (852) 2 191 3830
 Fax: (852) 2 389 5803

Data sheets are for initial product selection and comparison. Contact Esterline Power Systems prior to choosing a component.