



**Application:** Rail Transit Systems

**Function:** Controls on-board switching functions.

**Characteristics:** Includes hermetically-sealed, high shock and high vibration relays. Up to nine relay cassettes offering different switching configurations. Standard switching configurations available including double-throw contacts, double-break contacts or a mixture of the two front panel LED indicators. Standard 19-inch, 6-unit or 3-unit rack configuration

**Features:** Polarizing keys to ensure correct cassette insertion. Relay contacts tracked out with two connector pins to allow wiring of relays from one cassette to those situated elsewhere on the train. Optional front-mounted test connector for onsite diagnostic testing.



Featuring **LEACH**® power and control solutions  
[www.esterline.com](http://www.esterline.com)

**AMERICAS**  
 6900 Orangethorpe Ave.  
 P.O. Box 5032  
 Buena Park, CA 90622

Tel: (01) 714-736-7599  
 Fax: (01) 714-670-1145

**EUROPE**  
 2 Rue Goethe  
 57430 Sarralbe  
 France

Tel: (33) 3 87 97 31 01  
 Fax: (33) 3 87 97 96 86

**ASIA**  
 Units 602-603 6/F Lakeside 1  
 No.8 Science Park West Avenue  
 Phase Two, Hong Kong Science Park  
 Pak Shek Kok, Tai Po, N.T.  
 Hong Kong

Tel: (852) 2 191 3830  
 Fax: (852) 2 389 5803

Data sheets are for initial product selection and comparison. Contact Esterline Power Systems prior to choosing a component.